

[EXIT](#)[PRINT](#)[NEXT](#)*ELECTRIC GLOBE***205** SERIES**V A L V E S***ELECTRIC GLOBE***205** SERIES**V A L V E S**

The 205 Series 1-inch plastic valve is the irrigation industry's time-tested leader for dependable operation in potable and dirty water applications. With a proven track record of success in a wide range of environments, these debris-tolerant valves are available with flow control as an optional feature.

Constructed of heavy-duty, corrosion- and UV-resistant PVC, the 205 Series features a high-flow, low-friction-loss design that has a pressure range of 10-150 psi and flow range of 5-25 GPM. A manual bleed and a rugged, nylon-reinforced Buna-N diaphragm add to this valve's wide popularity.

The 205 Series — work horse performance from a thoroughbred body.

**Irritrol**<sup>®</sup>  
SYSTEMS



## 205 SERIES

## VALVES

1"

## plastic models

## Features

## Performance

- Flow range from 5-30 GPM
- Pressure range from 10-150 psi
- Manual external bleed
- Debris-tolerant design
- High flow, low-friction-loss design
- Optional flow control for precise flow adjustment and manual shutoff

## Quality Construction

- Heavy-duty, corrosion- and UV-resistant PVC construction
- Rugged, nylon-reinforced Buna-N diaphragm
- Encapsulated solenoid
- Available in female NPT or slip configuration
- Removable, tamper-resistant flow control handle
- Easily serviced without removal from the system

## Electrical Specifications

- Solenoid: 24 VAC
- Inrush volt-amp: 24 VAC-11.50 VA
- Inrush current: .4 amp
- Holding volt-amp: 24 VAC-5.75 VA
- Holding current: .2 amp


Flow Rate-GPM

Model	Size	2	5	10	15	20	30	40	Pressure Loss-PSI
205 Series	1"	3.82	3.00	2.20	1.90	3.10	5.10	11.40	

1) When designing a system, the industry standard for flow rate velocity through pipes and fittings is 5 FPS.

2) Pressure loss data are derived from valves independently tested by CIT, Fresno, CA.

## MODELS HOW TO SPECIFY



**Irritrol**  
SYSTEMS

BEYOND THE EXPECTED

5825 Jasmine Street, Riverside, CA 92504-1183  
909/785-3623 Fax 909/785-3795  
<http://www.irritrolsystems.com>